



120 rue de Naples, St Augustin de Desmaures, Qc, Canada, G3A 2Y2
P. 418.878.4116 F. 418.878.1595 Email : info@globaltardif.com

GT PERLA™ HDR Hydraulic 1:2 Home Lift Meets B613-00, B-44-04 Section 5.3 or ASME A18.1, ASME A.17.1

REQUEST FOR PRICING (RFP)

GT Accessibility
Update: October 29th 2006

Date : _____

Estimate #:
To be completed by Global Tardif

Company Name : _____

Job Name : _____

Contact name: _____

Location : _____

Telephone : _____

Fax : _____

NOTE: All completed RFP's can be either faxed to 418.878.1595 or emailed to info@globaltardif.com

General Information: Please visit our web at www.gtaccessibility.com for additional information

1.0 Model Base Package

GT PERLA HDR - Base package

Base package includes Car Doors Stainless Steel # 4, Cab Front return in Stainless steel # 4, Automatic door operator, KV1P valve.

1.1 Number of Stops

2 Stops

3 Stops

Other number of stops Specify Stops

1.2 Voltage

Standard Voltage for Motor & Control 575-600 V / 3 / 60

Standard Voltage for Motor & Control 208 or 480 V / 3 / 60

Optional - Voltage for Motor & Control 220 V / 1 / 60

1.3 Capacity (1= Yes)

750 lbs max @ 36 fpm

1000 lbs max @ 27 fpm

1.4 Pit Depth

Standard 8" (205 mm)

Other: Specify Inches

1.5 Overhead (minimum 96" for 80" high cab - if higher cab, add same increase in overhead)

Standard 108" without " Prop"

Optional " Top Prop "

Other above 108" Confirm exact dimension :

1.6 Total Travel

= total travel height in INCHES

1.7 Floor to floor travel between landing in inches

Between 1st to 2nd floor

Between 2nd to 3rd floor

Between 3rd to 4th floor

1.8 Guide Rails Sections

8 ft rail section **STANDARD**

16 ft rail section

1.9 Fasteners for rail brackets

Not required **STANDARD**
 Concrete anchors Lag bolts Through Bolts Specify with an "X"

2.0 Control room layout

Adjacent Machine Room
 Opposite Machine Room
 Rear Machine Room
 Remote Machine Room Specify feet Customer must provide a sketch for our engineering dept.

2.1 Configuration Model Type (go to www.gtaccessibility.com for more details)

PERLA-1 (Front only)
 PERLA-2 (Front/Rear)

2.2 Cab Size (all dimensions are approx. & may vary with the models selected)

Standard size	Perla-1			Perla-2		
Cab, size (WxD)	36"	x	54"	36"	x	48"
Hoistway size (WxD)	54"	x	74"	54"	x	83"

Other size up to 21 Sq. ft (where permitted) Confirm cab size : W: inches D: inches
 Other size up to 15 Sq. ft (B44 section 5.3) Confirm hoistway size : W: inches D: inches

3.1 THREE (3) Speed Entrances

Light Duty GT-CTA 3 Speed entrance - Track, hangers, closers & lock, Prime painted with Aluminum Extruded sill, satin coat fascias **-NOT UL/ ULC Fire Rated**
 Heavy Duty GT-ECONO 3Speed entrance - Hollow metal door panels, Track, hangers, closers & lock, Light grey prime painted with Aluminum Extruded sill, satin coat fascias **UL / ULC Fire Rated entrances**

*** All doors to be 32" (800mm) x 80" (2032 mm)*

Standard Frames built to suit 8" concrete block each
 Optional - Frames built to suit Drywall up to 8" each
 Optional - Frames built to suit very thick wall (Block or Drywall) up to 12" each

3.2 Entrances finishes Options

Painted entrance
 Stainless steel # 4 entrance or Stl/Stl # 8 mirror finish entrance Specify
 Bronze/ Muntz # 4 satin finish entrance or Bronze/ Muntz # 8 mirror finish entrance Specify

3.3 Entrances options

Option - To supply Nickel Silver sill each
 Option - To supply Bronze sill each
 If other specify:

4.0 Control operation

UPS Emergency Battery Lowering
 Constant Pressure operation - STANDARD
 Optional - Single Automatic *** Where permitted by Code

4.1 Controller options

Short Floor - Floor to floor lower than 12"
 ' Up " start counter
 Automatic " turn off " cab lighting

4.3 TRAVELLING CABLE

Not required - provided by others
 Provided by GT

4.4 Electrical Wiring material

Not required - provided by others
 Provided by GT

4.5 Electrical Conduit material *KIT - EMT PIPE*

Not required - provided by others
 Provided by GT

5.0 Type of Power unit

Standard " NON SUBMERSIBLE MOTOR " with submersible pump
 ' SUBMERSIBLE MOTOR " in lieu of dry motor w/ submersible pump

5.1 Hydraulic Valve option

Multi-Speed valve - Slow Up & Down speed EV100 valve

5.2 Hydraulic Oil

Not required - provided by others
 Hydraulic Oil supplied by GT **
*** GT will not ship to Canada or US any hydraulic oil - Only pick up at the plant*

5.3 Hydraulic hose line & fittings

Not required - provided by others
 Hydraulic hose line & fittings & flow control

6.0 CAB

Standard 6'-8" cab height - Stainless steel # 4 Cab front return, strike column & Car doors.
 Cab front to be Stainless steel # 8 mirror finish
 Cab front to be Bronze satin # 4 finish
 Cab front to be Bronze mirror # 8 finish
 Optional Custom cab height up to 9'-0" ** **Confirm exact cab height:** Inches
*** if higher cab is required, additional clear overhead of same increase will be required also.*

6.1 CAB Walls STANDARD

Standard steel shell walls Satin Coat Bare Steel Zinc coated
 Standard steel shell walls Optional Black Painted Optional White Painted **Specify**
 Plastic Laminate applied directly to cab shell - GT P. Lam. Selection Chart **Specify**
 Plastic Laminate hang on panels on Steel Shell - GT P. Lam. Selection Chart **Specify**
 Stainless Steel # 4 kick base Stainless Steel #4 Reveals **Specify**

6.2.A CAB Walls Options *** For B613 or B44 5.3 Application Only*

Modular St/Stl # 4 Cab walls framing with **Melamine** panel

<input type="checkbox"/> Unfinished MDF	<input type="checkbox"/> Bryan Maple # 687	<input type="checkbox"/> Pear # 971	<input type="checkbox"/> Nova White # 555	<input type="checkbox"/> Denim Maple # 391	<input type="checkbox"/> Lemon Wood # 393	<input type="checkbox"/> Porto # 965
---	--	-------------------------------------	---	--	---	--------------------------------------

6.2.B CAB Walls Options

Modular St/Stl # 4 Cab walls framing with **Plastic Lam. panel** GT Color Selection chart **Specify**
 Optional Standard Wilsonart selection Chart or other Plastic Laminate or any other special cab wall finishes
Specify

6.2.C CAB Options

Glass Wall - Side or Rear w/ clear laminated glass & Stainless # 4 framing
 Glass Wall - Side or Rear w/ clear laminated glass & Stainless # 8 framing
 Multi Beams light ray door detector

6.3 CAB Ceiling

Standard white melamine panel with (2) pot lights
 Ceiling finish to Stainless steel # 4 and P. Laminate
 Optional Bronze pot lights instead of typical white trim
 Other: **Specify**

6.4 CAB Handrails

<input type="checkbox"/>	Standard	Tubular 1 1/2" x 19" long - Stainless # 4 - Commercial design
<input type="checkbox"/>	Optional	Flat handrail 1/4" x 2" Stainless steel # 4
<input type="checkbox"/>	Optional	Flat handrail 1/4" x 2" Bronze # 4
<input type="checkbox"/>	Optional	Tubular 1 1/2" Stainless # 4 - Black flat end caps
<input type="checkbox"/>	Optional	Round hardwood 1 1/2"

6.7 CAB Flooring

<input type="checkbox"/>	Standard	Plywood - Two (2) layers
<input type="checkbox"/>		Rubber mat flooring - Amtico
<input type="checkbox"/>		1/8" (3 mm) floor recess thickness - finished flooring by others
	Specify	1/8" <input type="checkbox"/> 1/4" <input type="checkbox"/> 3/8" <input type="checkbox"/>

7.0 FIXTURES

<input type="checkbox"/>	Standard	COP
<input type="checkbox"/>	Option	Digital Car Position Indicator - Dot matrix
<input type="checkbox"/>	Optional	Rear Opening provision for button & operation.
<input type="checkbox"/>	Option	Brass COP and pushbuttons

7.1 Telephone

<input type="checkbox"/>	Standard telephone box (no phone)	Specify	Stainless # 4: <input type="checkbox"/>	Bronze # 4: <input type="checkbox"/>
<input type="checkbox"/>	Hands Free phone	Integrated in COP		

7.2 Hall Stations

<input type="checkbox"/>	Standard Residential	Keyless Call push button
<input type="checkbox"/>		Keyed Call station & Car here indicator
<input type="checkbox"/>	Add On -	OFF key
<input type="checkbox"/>	Add "	Door Open " if Automatic
<input type="checkbox"/>	Add an	Access key switch

7.3 Landing Designation

*** Standard designation available (SS, RC, B, G, L, M, 1, 2, 3, 4, 5)

9.0 CRATING

<input type="checkbox"/>	Un-crated material -	Pick up by Elevator Contractor at our plant
<input type="checkbox"/>	Crating on a	pallet
<input type="checkbox"/>	Crating in a wood box -	totally enclosed with plastic wrap protection
<input type="checkbox"/>	Overseas Crating -	wood treated

Clarifications, Comments or Alternate
