

## GT-VisionLift Hydraulic Price Request Form

120 rue de Naples St-Augustin de Desmaures Quebec, Canada P.: 1 800 661 6316

F.: 1 418 878 1595 Email: sales@globaltardif.com

Company:			To:				
Attention of:			Request Date:				
Telephone:		Quo	Quote required date:				
Fax:			Job Name				
E-Mail:							
	ırpose, shall we quote	our standard options wi					
1- MODEL							
Holed	Holeless Twin Jack direct	Holeless Twin Jack Telescopic	Holeless Twin Jack roped	Cantilever direct	Cantilever roped		
2- GENERAL SUMMARY							
Type of project:	New Building		Modernization				
	Passenger	Freight if freight, specify class of loading:					
Number of cars:	Simplex Hoistway configuration:	Duplex Triplex Group (How many:)					
Code Compliance:	ANSI 17.1-96 with add.	_	B44/A17.1 - 2004	Other:			
Seismic Requirement:	Zone 0 or 1	Zone 2	Zone 3				
Line Voltage:	208 / 3 / 60	<u> 480 / 3 / 60</u>	600 / 3 / 60	Other - Please spe	Other - Please specify :		
J	D	2100 LBS	2500 LBS	3000 LBS			
Canacitus	Passenger	☐ 3500 LBS	☐ 4000 LBS	Other:			
Capacity:	Hamital Time	3500 LBS	4000 LBS	4500 LBS			
	Hospital Type	☐ 5000 LBS	Other:				
Speed:	50 FPM	☐ 80 FPM	☐ 100 FPM	☐ 125 FPM			
	☐ 150 FPM	☐ 175 FPM	200 FPM	Other:			
Emergency Power:	☐ Building Generator		☐ Battery lowering device				
Machine room location	Adjacent to lowest land	ing Other, please advise :		Remote:			
	CAR # 1	CAR # 2	CAR #	# 3	CAR # 4		
Total Travel:							
Number of Landing:							
# of Front Openings:							
# of Rear Openings:							
# of Side Openings:							
Are the dimensions fixed	? YES NO	To Suit Global-Tardif Standards					
Hoistway Size:	(w) <b>X</b>	(d) (w) <b>X</b>	(d) (w) <b>&gt;</b>	<b>(</b> d)	(w) <b>X</b> (d)		
Pit Depth:	(w) A	(w) A	(w) /	·(u)	("/ ^(")		
Overhead Dimension:					_		
Overnoud Dimension.							
3- HYDRAULIC OPTIONS							
Pump:	525 - 600 PSI (Std)	400 PSI Max (Opt)	Dry type (with V-belt co	upling) Down speed regul	ated valve (Opt)		
Jack:	One-Section	Two Sections Three Sections					
Valves:	Additional Ball Valve in	Pit	☐ Pipe Rupture Valve (Seis	Pipe Rupture Valve (Seismic Zone only)			
Couplings / Strainers:	2x Isolation Couplings (	Opt)	Oil Line Strainer (Opt)	Oil Line Strainer (Opt)			
Tank Heater / Cooler:	Oil Heater (Opt)		Oil Cooler (Opt)	Oil Cooler (Opt)			
Miscellaneous:	Scavenger Pump (Opt)		Oil, Feedline and Fitting	s (by others)			
4- CONTROLLER:							
Controller Provisions:	Load Weighing	☐ Earthquake	Hall Lantern Interface	EMT (CMR524)			
Starter type	Anti-Nuisance	Security floor lock-out	☐ Blue Code				
Starter type	Accross the line	Y-Delta	Soft-Start				

5- DOOR EQUIPMENT / CAR ENG	CLOSURE:						
Cab Height:	8"-0" (2400 mm)(std)	8'-6" (2600 mm)	9'-0" (2744 mm)				
Cab Height.	9'-6" (2900 mm)	10'-0" (3048 mm)	Other:				
Door Operator(s):	Standard	Closed Loop VVVF Other:					
	☐ ECHO Cab St. Stl #4 Front, Return and Transom; St. Stl #4 Reveals and Kick Base; Removeable Wall Plastic Li				Laminates;		
	(Max Speed of 200 fpm)	White Pl .Lam Ceiling w/ 4 pot lights; St. Stl. Handrails; One Speed Fan					
		(Best Value in it's Category)					
Cab Type:	LSE4 or Pro-Cab	St. Stl #4 Front, Return and Transom; St. Stl #4 Reveals and Kick Base; Removeable Wall Plastic Laminates;					
oub Type.	(Max Speed of 200 fpm)	Eggcrate Ceiling w/ Fluoresecent Lighting; St. Stl. Handrails; Two Speed Fan					
		(Economical Option for it's Purpose)					
	Shell Cab Only	Finish by Other					
	Shell Cab	With the Following Options:					
	Front Return:	Fixed (std)	Swing (Expensive)				
	Gauge thickness:	16 Gauge (std)	14 Gauge				
	Returns / Transoms & Doors:	Stainless Steel #4 (std)	Stainless Steel #8	Bronze #4	Bronze #8		
	Reveals / Kickplate:	Stainless Steel #4 (std)	Stainless Steel #8	Bronze #4	Bronze #8		
	Wall Finish:	PI. Lam. Hang on Panel (std)	St. Stl Panel	Rigitex 5WL	U Other:		
	Ceilling Type:	GT22 - White Eggcrate (std) GT22L - Translucid Lexan Pl. Lam. Drop Ceiling w/ Peripherical Lighting					
		Down Light (please specify belo					
Cab Option:	Down Light Finish:	_	Stainless Steel #4 Stainless Steel #8 Mirror Muntz Satin #4				
	l les desiles	Bronze / Muntz #8 Mirror					
	Handrails:	Tubular 1 1/2" diam.	Flat 1/4" x 2"	Flat 1/4" x 4"	☐ Flat 1/4" x6"		
	Car Sill:	Aluminium (std)	Nickel Silver	Bronze	St. Steel		
	Ventilation:	Fan Two speed (std)	OFCE Dunlan December	Fan Three speed			
		Protective Pads	GFCF Duplex Receptacle	Halogen Lighting	and Delever Hearders!		
		Rear Glass Back above Handra	ii Only	Rear Glass Back Above a	nd Below Handrali		
6- ENTRANCES:							
o- ENTRANCES.	Single Speed	Centre Opening	Two Speed Side Opening				
Entrance Type:	Econo (include tracks, hangers,	· -					
■ Width		42"	48"	other:			
Entrance Size:		96"	☐ 108"	other:			
	Prime Coat Light Grey (std)	Stainless Steel #4	Bronze 60/40 Muntz #4				
Frame / Doors Finis  Main Floor:	Painted (Expensive)	Stainless Steel #8	Bronze 60/40 Muntz #8				
Entrance Sill		Nickel Silver	Stainless Steel	Bronze			
Frame / Doors Finis	Prime Coat Light Grey	Stainless Steel #4	Bronze 60/40 Muntz #4				
Typical Floor:	Painted (Expensive)	Stainless Steel #8	Bronze 60/40 Muntz #8				
Entrance Sill	ı: Aluminium	Nickel Silver	Stainless Steel	Bronze			
Entrance Frame:	Three (3) Piece Bolted 2 " Profil	e (std)	Welded	Welded and Mitered			
Entrance Wall Thickness:	Std Wall Type is 8" Masonry - if	other specify:	☐ Drywall	Masonry Thickness:			
7- FIXTURES:							
Fixture Type:	US92 (std)	US 20AW (VR) (std)	US 91 (VR)				
,	US 90-15 / US 91-15	US 91BB	US 93 (Tamper Proof)				
Car Faceplate Finish:	Stainless Steel #4 (std)	Stainless Steel #8	Bronze 60/40 Muntz #4	Bronze 60/40 Muntz #8			
Hall Faceplate	Stainless Steel #4 (std)	Stainless Steel #8	Bronze 60/40 Muntz #4	Bronze 60/40 Muntz #8			
Graphics: (Extra Cost)	Do not use elevator in case of		Appendix O - Graphic & signa	ge			
Car Operating Panels:	Main Only	Main & Auxilliary					
Communication:	Hands Free Phone	☐ Phone Cabinet Only (for phone by others) ☐ By others - provision only					
Signal Devices:	Car Riding Lanterns - std arrow t						
Hall Position Indicator:	☐ Main/Lobby Only     ☐ Other floor Specify qty:						
Fixture Options:	COP Service Cabinet	Lobby Panel	Remote Fire Control Panel	Hall Call Lockout Switch Qty:  Hall Call Lockout Switch Qty:			
	COP Pre-wiring (Extra)	Card Reader in COP (Provision	Uniy)	Hall Call Lockout Switch	uty:		
Expected delivery date of the	he material:						
8- COMMENTS:							
	Please vis	sit our Web Site WWW.	GlobalTardif.com				
1							