

120 rue de Naples, St Augustin de Desmaures, Qc, Canada, G3A 2Y2 P. 418.878.4116 F. 418.878.1595 Email : info@globaltardif.com

GT100C HD Commercial Wheelchair Lift CSA B355-09 & ASME A.18.1

REQUEST FOR PRICING (RFP)

GT Accessibility
Update: 2011-05-31

Date :	Estimate #: To be completed by Global Tardif			
Company Name :	Job Name :			
Contact name:	Location :			
Telephone :	Fax :			
NOTE: All completed RFP's can be either faxe	ed to 418.878.1595 or emailed to sales@globaltardif.com			
General Information: Please visit ou	ur web at www.globaltardif.com for additional information			
Applicable Codes including Local :				
1.0 Model Base Package				
	n speed only) raulic 2:1 package, complete power unit with screw ve KV1P, constant pressure operation. (NO CAB)			
1.1 Number of Stops				
2 Stops				
3 Stops				
Other number of stops				
1.2 Voltage Voltage for Motor & Control STANDARD	220 V / 1 / 60			
Voltage for Motor & Control	575-600 V / 3 / 60			
Voltage for Motor & Control	208 or 480 V / 3 / 60			
1.3 Capacity				
1000 lbs max @ 30 fpm				
1.4 Pit Depth				
Standard 10" (254 mm)				
Other: Specified:	Inches			
1.5 Overhead (minimum 92" for 80" high cab	- if higher cab, add same increase in overhead)			
Standard minimum 96" (2438 mm)				
Overhead: Other Confirm ex	xact dimension :			
1.6 Total Travel				
= total travel height in INCHES				
1.7 Guide Rails Sections				
8 ft rail section STANDARD				
16 ft rail section				

1.9	_Machine room layout				
	Adjacent Machine Room				
	Opposite Machine Room				
	Rear Machine Room				
	Remote Control Room Specified: feet Customer must provide a sketch for our engineering dept.				
2.0	CAB				
2.1	Configuration Model Type				
	GT 101 (Front only) GT 102 (Front/Rear) GT 103 (Front/Side) GT 104 (Side only)				
2.2	Cab Size (all dimensions are approx. & may vary with the models selected)				
	Standard size GT 101C GT 102C GT 103C GT 104C				
	Cab, size (WxD) 36" x 62" 36" x 63" 36" x 60" 60" x 36"				
	Hoistway size (WxD) 54" x 65" 54" x 64" 54" x 66" 68" x 54"				
	Other size up to 21 Sq. ft (where permitted) Confirm cab size : W: inches D: inches				
	Confirm hoistway size : W: inches D: inches				
2.3	CAB Height				
1	Standard 6'-8" cab height				
	Optional Custom cab height up to 8'-0" Confirm exact cab height:				
	** if higher cab is required, additional clear overhead of same increase will be required also.				
2.4.0	CAB Inside fFinish				
	M Serie - Melamine Panels Serie 3/4" melamine panels, ceiling is white melamine with two (2) recessed pot light fixture and plastic eggcrate inserts				
	Unfinished MDF Particule Board (Medium density)				
	Standard Melamine Hardrock Maple # 992				
	Standard Melamine Classic Cherry # 314				
	Additional " add on " above Cab package selection above				
	Hiteak # 511 Sweet Beige # 520 Bryan Maple # 687 Inspiration # 744				
	Urban Mahogany # 838 Sheen Linen # G20 Coastal Pear # G23				
	PL Serie - Plastic Laminate Panels Serie				
	3/4" plastic laminate panels, ceiling is white melamine with two (2) recessed pot light fixture and				
	plastic eggcrate inserts				
	Global Tardif Standard Wilsonhart Plastic Laminate selection Chart (32 colors)				
	Other Wilsonart Plastic laminates (overall choice 240) Specify: Specify: Specify:				
	Custom Plastic Lam. or any other special cab walls finishes Specify: Other Standard plastic laminate - Max. \$ 4.00 per Sq. ft Specify:				
	Other Standard plastic laminate - Max. \$ 4.00 per Sq. ft Custom Plastic Laminate or any other special cab walls finishes Specify: Specify:				
	Todaton Flactic Editinate of any other operations with minorites and the second case wants innovince and the second case wants in second case wants in second case wants in second case with the second case wants in second case wants in second case with the second case wants in second case with the second case wants in second case with the second case wi				
	Additional Cab Wall Options				
	Glass Wall - Side or Rear wall w/ clear Lam. Safety glass - Aluminum framing				
	Glass Wall - Side or Rear wall w/ clear Lam. Safety glass with stainless # 4 framing Glass Wall - Side or Rear wall w/ clear Lam. Safety glass stainless # 8 framing				
	Glass Wall - Side or Rear wall w/ clear Lam. Safety glass Satin Bronze framing				
2.4.1	Optional " Mirror panel " - Above handrail height - per mirror Cab Ceiling and Cab lighting				
2.4.1	T				
	Standard white melamine with (2) pot lights				
	Optional Bronze pot lights instead of typical white trim				

2.4.2	CAB Handra	ils					
	Standard		- St/Stl #4 Tubular 1 1/4"	- 18" I G			
	Optional	Flat handrail 1/4" x 2		- 10 LO			
	1 '						
	Optional	Flat handrail 1/4" x 2					
	Optional		ess # 4 - Black flat end c	•			
	Optional	Tubular 1 1/2" Polish	ed Stainless # 8 Mirror fir	nish - Black flat er	nd caps		
	Optional	Tubular 1 1/2" Bronz	e satin # 4 - Black flat er	nd caps			
	Optional		e Mirror - Flat end caps				
2.4.5	CAB Floorin	g					
	Standard Unfinished Plywood - Two (2) layers - 1 1/4" thick total						
	Optional Hard	dwood floor (Dark or li	ght oak, maple)				
		looring - Amtico					
3.0	Landing S	_					
			- Series GT-C10 - Stand 5" (914mm) x 80" (2032		d 1 1/2 hr Zinc coate	d w/ vision glass, clo	sers , Prudhomme
			GT-MT01 - HEAVY DU T	•	hr Zinc coated w/ v	ision glass closers	GAL Type N lock -
) x 80" (2032 mm)		1101010101112	I III Ziilo oodtod III V	iolori giaco, ciocoro ,	O/ IL Typo IT look
3.1	Custom en	trances & Options	3				
	GT-Swing Door	*** Alu. Frame	Plexiglass insert	Prud'homme lock	36" (914mm)		
	GT-Swing Door	*** Alu. Frame	Lexan insert	Prud'homme lock	36" (914mm)		
	GT-Swing Door	*** Alu. Frame	Tempered/ Lam Glass	Prud'homme lock	36" (914mm)		
	Additional Co	st to provide " Clear a	anodized Aluminum " GT	Swing Door framing	g		
	Custom GT S	T Swing door - St/Stl # 4 framing with laminated glass & pivots at top & bottom, w/					
		•	ype " N" Lock - 36" (914				
			wing door - Laminated/Te rud'home Lock - 36" (914				
	Motorized Re	tiring Cam for intermed	liate level. (Not required b	oy Code)			
3.2	Landing do	oor options					
	Option to provide - Stainless steel kick plate at bottom of door, hoistway side only						
	Custom paint	color * For GT-	Swing Door or GT-Swing	Gate			
	Brass kickplate and push plate (instead of stainless) Aluminum checker plate sill ** Available only with our HEAVY DUTY swing door						
	- 	Inlock the Interlock	18 77 - 1 - 12 - 7				
	<u>.</u>	Interlock ONLY	When landing entrance				
	7		Y When landing entra	inces are provided in Hunter/ Portro			
	4	or operator - On surfa perator- Recessed in		nunter/ Portio	DI IIK # 4200		
	-	er specify:	llooring				
4.1	Controller						
	7	ncy Battery Lowering	(included in base pa	ackage)			
	7	Floor to floor lower th	•	3 /			
	" Up" start co						
5.0		urn off " cab lighting AL EQUIPMENT					
	-	ole Not required - prov	ided by others				
	Travelling cable provided by GT Electrical Wiring Not required - provided by others						
	Electrical wiri	ng material provided b	y GT				
	Electrical Cor	nduit Not required - pro	ovided by others				
1	l						

Electrical Conduit & junction boxes (EMT & Duct) provided by GT

6.0	_Type of Power unit					
	Standard " NONE SUBMERSIBLE MOTOR " with submersible pump					
	If "SUBMERSIBLE MOTOR" instead of dry motor w/ submersible pump					
6.1	Hydraulic Valve option					
	Multi-Speed valve - Slow Up & Down speed EV100 valve					
6.2	Hydraulic Oil					
	Not required - provided by others					
	Hydraulic Oil supplied by GT **					
6.2	** GT will not ship to Canada or US any hydraulic oil - Only pick up at the plant					
6.3	Hydraulic hose line & fittings					
	Not required - provided by others					
7.0	Hydraulic hose line, fittings & flow control provided by GT FIXTURES					
7.0	All Car Operating Panel (C.O.P.) include emergency car lighting, floor selection buttons, Stop &					
	Alarm push button.					
	All hall stations are surface mount and contain " In Use " light and "					
	Standard COP					
	Optional Digital Car Position Indicator - Dot matrix					
	Optional Rear Opening provision for button operation.					
	Optional Brass COP and pushbuttons					
7.1	Telephone					
	Standard telephone box (no phone) Stainless # 4: Bronze # 4: Specify:					
	Hands Free phone Integrated in COP					
7.2	Hall Stations (specify number of:)					
	Standard Keyless Call push button					
	Keyless Call push button & Car here indicator					
	Keyed Call station & Car here indicator					
	Add On - OFF key					
	Add " Door Open " if Automatic					
	Add wheelchair " logo " on faceplate					
8.0	MISCELLANEOUS					
8.1	Fasteners for rail brackets - Select only one (1= Yes)					
	Not required STANDARD					
	Concrete anchors Lag bolts Through Bolts Specify with an "X"					
8.2	Other Miscellaneous					
	Pre-Cut & Washed rails					
	Split Cylinder Up-charges					
9.0	CRATING					
	Un-crated material - Pick up by Elevator Contractor at our plant					
	Crating on a pallet					
	Crating in a wood box - totally enclosed with plastic wrap protection					
	Overseas Crating - wood treated					
<u>Clar</u>	ifications, Comments or Alternate					