




Speed fpm (m/s)	Minimum Overhead ⁴	Maximum Travel	Pit Depth
	OH	OH	P
150-200 (0.75-1)	17'-6" (5335 mm)	150'-0" (45720 mm)	5'-6" (1675 mm)
250-350 (1.25-1.75)	18'-4" (5590 mm)	200'-0" (60960 mm)	
400 (2)	18'-9" (5715 mm)	350'-0" (106680 mm)	6'-0" (1830 mm)
450 (2.25)	20'-0" (6095 mm)	425'-0" (129540 mm)	
500 (2.5)	20'-0" (6095 mm)	450'-0" (137160 mm)	6'-6" (1980 mm)

Type of Opening	Capacity lbs (kg)	Speed fpm (m/s)	Hoistway Width		Hoistway Depth	Platform		Cab Inside Width	Cab Inside Depth	Clear Opening
			HW ⁵	DHW ⁵		PW	PD			
2SP	4000 (1800)	150-500 (0.75-2.5)	7'-8" (2340)	15'-8" (4775)	9'-9" (2970)	5'-8" (1730)	8'-10 1/2" (2705)	5'-4" (1626)	7'-11" (2413)	4'-0" (1220)
2SP	4500 (2000)	150-500 (0.75-2.5)	8'-0" (2440)	16'-4" (4980)	9'-9" (2970)	6'-0" (1830)	8'-10 1/2" (2705)	5'-8" (1727)	7'-11" (2413)	4'-0" (1220)
2SP	5000 (2250)	150-500 (0.75-2.5)	8'-3" (2515)	16'-10" (5130)	10'-4" (3150)	6'-3" (1905)	9'-5 1/2" (2885)	5'-11" (1803)	8'-6" (2591)	4'-6" (1370)

For seismic conditions zone 2 and greater add to dimension (in)[mm]	HW	4" (100 mm)
	HD	1" (25 mm)
	HW Rear Opening	3" (75 mm)

Project : _____

Location: _____

Traction Geared Above/Beside HOSPITAL TYPE - Duplex 2-Speed Front Opening

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group